



The attached gaseous oxygen MSDS may be used for the following series of AVOX Systems oxygen breathing equipment:

GST
15-40F
25200
28100
32000
3552
3553
5500
5600
588-125
588-145
6350
800112
800378
800425
801293
801307
802895
803240
803358
803668-01
803675
804044
891
892000
894
895
896
897
898
9000
9000A
900019
9700
9800



MATERIAL SAFETY DATA SHEET

PRODUCT NAME: OXYGEN

1. Product and Company Identification

BOC Gases,
Division of,
The BOC Group, Inc.
575 Mountain Avenue
Murray Hill, NJ 07974

BOC Gases
Division of
BOC Canada Limited
5975 Falbourne Street, Unit 2
Mississauga, Ontario L5R 3W6

TELEPHONE NUMBER: (908) 464-8100

24-HOUR EMERGENCY TELEPHONE NUMBER:
CHEMTREC (800) 424-9300

TELEPHONE NUMBER: (905) 501-1700

24-HOUR EMERGENCY TELEPHONE NUMBER:
(905) 501-0802

EMERGENCY RESPONSE PLAN NO: 2-0101

PRODUCT NAME: OXYGEN

CHEMICAL NAME: Oxygen

COMMON NAMES/SYNONYMS: None

TDG (Canada) CLASSIFICATION: 2.2 (5.1)

WHMIS CLASSIFICATION: A, C

PREPARED BY: Loss Control (908)464-8100/(905)501-1700

PREPARATION DATE: 6/1/95

REVIEW DATES: 11/11/03

2. Composition, Information on Ingredients

EXPOSURE LIMITS¹:

INGREDIENT	% VOLUME	PEL-OSHA ²	TLV-ACGIH ³	LD ₅₀ or LC ₅₀ Route/Species
Oxygen FORMULA: O ₂ CAS: 7782-44-7 RTECS #: RS2060000	99.6 to 100.0	Not Applicable	Not Applicable	Not Available

¹ Refer to individual state or provincial regulations, as applicable, for limits which may be more stringent than those listed here.

² As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993)

³ As stated in the ACGIH 2003 Threshold Limit Values for Chemical Substances and Physical Agents.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

3. Hazards Identification

EMERGENCY OVERVIEW

Odorless, colorless, non-flammable gas. Oxidizer. Will accelerate combustion and increase the risk of fire and explosion in combustible or flammable materials. Non-toxic. Prolonged inhalation of high concentrations may cause coughing and lung effects. Contents under pressure. Use and store below 125 °F.

MSDS: G-1

Revised: 11/11/03

Page 1 of 7

PRODUCT NAME: OXYGEN

ROUTE OF ENTRY:

Skin Contact No	Skin Absorption No	Eye Contact No	Inhalation Yes	Ingestion No
--------------------	-----------------------	-------------------	-------------------	-----------------

HEALTH EFFECTS:

Exposure Limits No	Irritant No	Sensitization No
Teratogen No	Reproductive Hazard No	Mutagen No
Synergistic Effects None known		

Carcinogenicity: -- NTP: No IARC: No OSHA: No

EYE EFFECTS: Harmful effects are not expected.

SKIN EFFECTS: Harmful effects are not expected.

INGESTION EFFECTS: Not applicable. Product is a gas.

INHALATION EFFECTS: Oxygen is not acutely toxic under normal pressure. Prolonged inhalation of high oxygen concentrations (> 75%) may affect coordination, attention, and cause tiredness or respiratory irritation. Inhalation for several hours may cause cough, sore throat, chest pain and difficulty breathing.

Oxygen is more toxic when inhaled at elevated pressures. Depending upon pressure and duration of exposure, pure oxygen at elevated pressures (i.e.: divers) may cause cramps, dizziness, difficulty breathing, convulsions, edema, and death.

Elevated oxygen concentrations in incubators has caused visual impairment and blindness in premature infants. High oxygen concentrations primarily affect eyes which are not fully developed (see Section 11).

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: May aggravate chronic obstructive pulmonary (lung) disease.

POTENTIAL ENVIRONMENTAL EFFECTS: Not expected to be toxic to fish and wildlife.

4. First Aid Measures

EYES: None required.

SKIN: None required.

INGESTION: None required.

INHALATION: Overexposure to oxygen is not anticipated under normal working conditions. High oxygen concentrations in the air may present a fire and explosion hazard. PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES WHEN OXYGEN IS INHALED UNDER PRESSURE (i.e.: as in scuba diving). Conscious persons should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Further treatment should be symptomatic and supportive. Inform the treating physician that the patient could be experiencing hyperoxia.

PRODUCT NAME: OXYGEN

5. Fire Fighting Measures

Conditions of Flammability: Not flammable, Oxidizer		
Flash point: None	Method: Not Applicable	Autoignition Temperature: None
LEL(%): None		UEL(%): None
Hazardous combustion products: None		
Sensitivity to mechanical shock: None		
Sensitivity to static discharge: None		

FIRE AND EXPLOSION HAZARDS: High oxygen concentrations vigorously accelerate combustion. Will support or initiate combustion/ explosion of organic matter and other oxidizable material. Cylinder may vent rapidly or rupture violently from pressure when involved in a fire situation.

EXTINGUISHING MEDIA: Water spray to keep cylinders cool. Extinguishing agent appropriate for the combustible material.

FIRE FIGHTING INSTRUCTIONS: If possible, stop the flow of oxygen which is supporting the fire. Firefighters should wear respiratory protection (SCBA) and full turnout or Bunker gear. Continue to cool fire-exposed containers until well after flames are extinguished.

6. Accidental Release Measures

Evacuate all personnel from affected area. A leak near combustible or flammable materials may represent a severe fire or explosion hazard. Eliminate all ignition sources. Ventilate enclosed areas. If it can be done without risk, stop the flow of gas or remove cylinder to outside. Use appropriate protective equipment (See Section 8). If leak is in user's equipment, be certain to purge piping with inert gas prior to attempting repairs. If leak is in container or container valve, contact the appropriate emergency telephone number listed in Section 1 or call your closest BOC location.

7. Handling and Storage

Electrical classification: Nonhazardous

Dry product is noncorrosive and may be used with all materials of construction. Moisture causes metal oxides which are formed with air to be hydrated so that they include volume and lose their protective role (rust formation). Concentrations of SO₂, Cl₂, salt, etc. in the moisture enhances the rusting of metals in air. Carbon steels and low alloy steels are acceptable for use at lower pressures.

For high pressure applications stainless steels are acceptable as are copper and its alloys, nickel and its alloys, brass bronze, silicon alloys, Monel®, Inconel® and beryllium. Lead and silver or lead tin alloys are good gasket materials. Teflon®, Teflon® composites, or Kel-F® are preferred non-metallic gasket materials.

Oxygen should not be used as a substitute for compressed air in pneumatic equipment since this type generally contains flammable lubricants. Equipment to contain oxygen must be "cleaned for oxygen service". Check with the supplier to verify oxygen compatibility for the service conditions.

Stationary customer site vessels should operate in accordance with the manufacturer's and BOC's instruction. Do not attempt to repair, adjust or in any other way modify the operation of these vessels. If there is a malfunction or other type of operations problem with the vessel, contact the closest BOC location immediately. Valve protection caps must remain in place unless container is secured with valve outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure reducing regulator when connecting cylinder to lower pressure piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the system. Do not insert any object (i.e.: screwdriver) into valve cap openings as this can damage the valve causing leakage.

Protect cylinders from physical damage. Store in cool, dry, well-ventilated area away from heavily trafficked areas, emergency exits, flammables and combustibles. Do not allow the temperature where cylinders are stored to exceed 125°F (52°C). Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in-first out" inventory system to prevent full cylinders being stored for excessive periods of time. Post "NO SMOKING OR OPEN FLAMES" signs in the storage area or use area. There should be no sources of ignition in the storage or use area.

For additional storage recommendations, consult Compressed Gas Association's Pamphlets SB-7, G 4.3, G4.1, G-4.4, P-2.5, P-2.6, G-4.9, P-14, P-1, SB-2.

Do not release in a confined area. Never carry a compressed gas cylinder or a container of a gas in cryogenic liquid form in an enclosed space such as a car trunk, van or station wagon. A leak can result in a fire, explosion, or a toxic exposure.

8. Exposure Controls, Personal Protection

ENGINEERING CONTROLS: Use general ventilation and/or local exhaust as necessary to keep oxygen concentrations below 23.5%.

EYE/FACE PROTECTION: Safety goggles or glasses as appropriate for the job.

SKIN PROTECTION: Protective gloves made of any suitable material appropriate for the job. Gloves must be clean and free from oil and grease.

OTHER/GENERAL PROTECTION: Safety shoes.

9. Physical and Chemical Properties

PARAMETER	VALUE	UNITS
Physical state (gas, liquid, solid)	: Gas	
Vapor pressure	: Above critical temp.	
Vapor density (Air = 1)	: 1.11	
Evaporation point	: Not Available	
Boiling point	: -297.3	°F
	: -182.9	°C
Freezing point	: -361.8	°F
	: -218.8	°C
pH	: Not Applicable	
Specific gravity at STP	: Not Available	
Oil/water partition coefficient	: Not Available	
Solubility (H ₂ O)	: Slight 0.0491	v/v @ 32 °F; 0 °C
Odor threshold	: Not Applicable	
Odor and appearance	: Colorless, odorless gas	

10. Stability and Reactivity

STABILITY: Stable.

INCOMPATIBLE MATERIALS/CONDITIONS: All flammable, organic, and combustible materials. Avoid heat, sparks, flames, and other ignition sources.

HAZARDOUS DECOMPOSITION PRODUCTS: None.

HAZARDOUS POLYMERIZATION: Will not occur.

11. Toxicological Information

SKIN AND EYE:

The incompletely developed retinal circulation is more susceptible to toxic levels of oxygen. In premature infants, arterial oxygen tension above 150 mm Hg may cause retrolental fibroplasia. Permanent blindness may occur several months later. One case of severe retinal damage in an adult was reported. An individual suffering from myasthenia gravis developed irreversible retinal atrophy after breathing 80% oxygen for 150 days.

INHALATION:

Human volunteers which inhaled 90-95% oxygen through a face mask for 6 hours showed signs of tracheal irritation and fatigue. Other symptoms (which might have been caused by placing a tube into the trachea during the experiment) included: sinusitis, conjunctivitis, fever, and symptoms of acute bronchitis.

Poisoning began in dogs 36 hours after inhalation of pure oxygen at atmospheric pressure. Distress was seen within 48 hours and death within 60 hours.

PRODUCT NAME: OXYGEN

12. Ecological Information

Product does not contain Class I or Class II ozone depleting substances. Not toxic. Will not bioconcentrate.

13. Disposal Considerations

Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container PROPERLY LABELED, WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE to BOC Gases or authorized distributor for proper disposal.

14. Transport Information

PARAMETER	United States DOT	Canada TDG
PROPER SHIPPING NAME:	Oxygen, compressed	Oxygen, compressed
HAZARD CLASS:	2.2 (5.1)	2.2 (5.1)
IDENTIFICATION NUMBER:	UN 1072	UN 1072
SHIPPING LABEL:	NONFLAMMABLE GAS, OXIDIZER	NONFLAMMABLE GAS, OXIDIZER

15. Regulatory Information

SARA TITLE III NOTIFICATIONS AND INFORMATION

SARA 313: This product does not contain ingredients subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 49 CFR Part 372.

SARA TITLE III - HAZARD CLASSES:

Fire Hazard

Sudden Release of Pressure Hazard

U.S. TSCA/Canadian DSL: All ingredients are listed on the U.S. Toxic Substances Control Act (TSCA) inventory or exempt from listing and on the Canadian Domestic Substance List (DSL).

California Proposition 65: This product does not contain ingredient(s) known to the State of California to cause cancer or reproductive toxicity.

Canadian Controlled Products Regulations (CPR): This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

16. Other Information

NFPA HAZARD CODES

Health: 0
Flammability: 0
Instability: 0

OXIDIZER

HMIS HAZARD CODES

Health: 0
Flammability: 0
Reactivity: 0

RATINGS SYSTEM

0 = No Hazard
1 = Slight Hazard
2 = Moderate Hazard
3 = Serious Hazard
4 = Severe Hazard

MSDS: G-1

Revised: 11/11/03

PRODUCT NAME: OXYGEN

Note: The Reactivity Hazard Rating is based on the 2nd Edition of the National Paint and Coatings Association's (NPCA's) Hazardous Materials Identification System (HMIS[®]). Hazard ratings were based on the best available information at the time of the review. Ratings will be reassigned in accordance with Compressed Gas Association (CGA) guidelines as published in the future edition of CGA Pamphlet P-19.

ACGIH	American Conference of Governmental Industrial Hygienists
DOT	Department of Transportation
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
SARA	Superfund Amendments and Reauthorization Act
STEL	Short Term Exposure Limit
TDG	Transportation of Dangerous Goods
TLV	Threshold Limit Value
WHMIS	Workplace Hazardous Materials Information System

Compressed gas cylinders shall not be refilled without the express written permission of the owner. Shipment of a compressed gas cylinder which has not been filled by the owner or with his/her (written) consent is a violation of transportation regulations.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).